PINIACLE Water Treatment

KLM Water Softener

When water quality matters, Pinnacle residential water softeners and filtration systems deliver. Featuring Pentair's patented Fleck technology and backed by superior after-sales support, Pinnacle systems are designed with Canadian families in mind.

Enhance the quality of your water with the Autotrol 762/255 Electronic Residential Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

Water treatment solutions engineered for your unique water needs.










Autotrol 762/255 Residential Water Softener

FEATURES

- 5-cycle programming
- Fast-positioning, reversible 10,000 RPM 12-volt DC drive motor
- Seal and spacer cartridge for easy servicing
- LCD backlit display for low-light conditions
- Precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Programming memory backup in case of power loss/outages

SYSTEM INCLUDES

- Control valve featuring SXT electronic timer
- ¾" paddle water meter
- ¾" MPT poly bypass assembly and Pentair poly glass media vessel with 1" ABS internal distribution
- Brine tank c/w salt shelf and Fleck 2310 brine safety float assembly
- Uses cation exchange resin



SPECIFICATIONS

| Model Number | Resin (CuFt) | Tank Sizes | | Unit Cap | | Flow Rates | | BKW | Salt | | Weight |
|-----------------|-----------------|------------|------------|----------|-----|------------|--|-----|------|----|--------|
| | | Resin Tank | Brine Tank | Min | Max | Service | | | 10 | 15 | |
| 24KLM | 0.75 | 8" x 44" | 14" x 34" | 18K | 24K | 4 | | 1.5 | 6 | 12 | 85 |
| 30KLM | 1.0 | 9" x 48" | 14" x 34" | 24K | 30K | 5 | | 2.0 | 7 | 15 | 95 |
| 40KLM | 1.3 | 10" x 47" | 14" x 34"" | 32K | 40K | 5.5 | | 2.4 | 8 | 20 | 125 |
| 60KLM | 2 | 12" x 52" | 18" x 40" | 48K | 60K | 6.5 | | 3.5 | 14 | 30 | 170 |
| 90KLM | 3 | 14" x 65" | 18" x 40" | 72K | 90K | 6.5 | | 4.0 | 21 | 45 | 225 |

Capacities are based on resin manufacturer's data ● Units are set to the factory minimum salt setting ● Use minimum capacity when sizing ● Flow rates are in U.S. Gallons/minute ● Sizes and space requirements are in inches





www.summitwater.ca



sales@summitwater.ca



