

PINNACLE

Water Treatment

Performa 762/268 Water Softener

When water quality matters, Pinnacle residential water softeners and filtration systems deliver. Featuring Pentair's patented Autotrol technology and backed by superior after-sales support, Pinnacle systems are designed with Canadian families in mind.

Enhance the quality of your water with the Autotrol Performa 762/268 Electronic Control Residential Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

**Water treatment solutions engineered
for your unique water needs.**



Autotrol Performa 762/268

Residential Water Softener

FEATURES

- DuraFlow valve disk operation which seats vertical to provide frictionless sealing
- Fully adjustable 5 or 8 cycle control
- Designed with double backwash for reduced hardness leakage
- Optical sensor for precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Programming memory backup in case of power loss/outages

SYSTEM INCLUDES

- Control valve featuring 762 professional level electronic timer
- 3/4" water meter
- poly bypass w/ 3/4" copper tail-kit assembly
- Pentair poly glass media vessel with 1" ABS internal distribution
- 28-gallon brine tank with salt shelf & brine safety float assembly.
- Uses high purity, premium-grade cation exchange resin



SPECIFICATIONS

| Model Number | Resin (CuFt) | Tank Sizes | | Unit Cap | | Flow Rates | | BKW (GPM) | Salt | | Weight (lbs) |
|--------------|--------------|------------|------------|----------|-----|------------|------|-----------|------|----|--------------|
| | | Resin Tank | Brine Tank | Min | Max | Service | Peak | | 10 | 15 | |
| 24KPLM | 0.75 | 8" x 44" | 14" x 34" | 18K | 24K | 4 | 8 | 1.5 | 8 | 12 | 85 |
| 30KPLM | 1.0 | 9" x 48" | 14" x 34" | 24K | 30K | 5 | 10 | 2.0 | 10 | 15 | 95 |
| 40KPLM | 1.3 | 10" x 47" | 14" x 34" | 32K | 40K | 5.5 | 11 | 2.4 | 13 | 20 | 125 |
| 60KPLM | 2 | 12" x 52" | 18" x 40" | 48K | 60K | 6.5 | 13 | 3.5 | 20 | 30 | 170 |
| 90KPLM | 3 | 14" x 65" | 18" x 40" | 72K | 90K | 6.5 | 13 | 4.0 | 30 | 60 | 225 |

Capacities are based on resin manufacturer's data • Units are set to the factory minimum salt setting • Use minimum capacity when sizing • Flow rates are in U.S. Gallons/minute • Sizes and space requirements are in inches

SUMMIT
WATER



www.summitwater.ca



519-843-4232



sales@summitwater.ca



Summit Water