

Pinnacle Filter Housing

FEATURES

- Suitable for residential, commercial, and industrial use
- Available in 10" and 20" lengths
- Thick, durable housing with leak-proof seal
- Optional pressure relief/bleed button on inlet side
- Clear or opaque sump options
- Accepts 2.5" or 4.5" diameter cartridges
- EPDM double O-ring design
- Reinforced brass ports



SPECIFICATIONS

- Housing: Polypropylene (opaque) or Styrene Acrylonitrile (clear)
- Cap: Reinforced polypropylene (HFPP)
- Pressure relief assembly: 300-series stainless steel, EPDM, polypropylene
- Temperature Rating: 40–100°F (4.4–37.8°C)
- Working Pressure: 30-80 psi (2.1-5.5 bar)
- Comes with wrench, bracket & screws



SPECIFICATIONS & PERFORMANCE

Part Number	Description	Filter Size Dimensions	Maximum Working Pressure	Port Size
FH-2510-CL-07	Pinnacle Filter Housing, Clear	2.5" x 10"	80 psi	3/4"
FH-2510-BL-07	Pinnacle Filter Housing, Blue	2.5" x 10"	80 psi	3/4"
FH-2520-BL-07	Pinnacle Filter Housing, Blue	2.5" x 20"	80 psi	3/4"
FH-4510-BL-10	Pinnacle Filter Housing, Blue	4.5" x 10"	80 psi	1"
FH-4520-BL-10	Pinnacle Filter Housing, Blue	4.5" x 20"	80 psi	1"
FHD-4520-BL-10	Pinnacle Dual Filter Housing, Blue	4.5" x 20"	80 psi	1"