

Pinnacle Filter Cartridge – Pleated Sediment

FEATURES

- Special formulation of resin-impregnated cellulose and polyester fibres
- Lengths: 10", 20"
- Provides higher wet strength than regular cellulose cartridges
- Minimal unloading and media migration
- Nominal 20, 30, 50-micron rating

SPECIFICATIONS

- Cellulose polyester filter fabric
- Vinyl plastisol 2.5" endcaps
- Polypropylene 4" endcaps
- Core polypropylene
- Temperature rating 41-113°F (5-45°C)



SPECIFICATIONS & PERFORMANCE

Part Number	Maximum Dimensions	Rating (Nominal)
SED-PLT-2510-30	2.5" x 10"	30 Micron
SED-PLT-2510-50	2.5" x 10"	50 Micron
SED-PLT-2520-30	2.5" x 20"	30 Micron
SED-PLT-2520-50	2.5" x 20"	20 Micron
SED-PLT-2520-20	2.5" x 20"	30 Micron
SED-PLT-4510-30	4.5" x 10"	30 Micron
SED-PLT-4510-50	4.5" x 10"	50 Micron
SED-PLT-4520-30	4.5" x 20"	30 Micron
SED-PLT-4520-50	4.5" x 20"	50 Micron