

PINNACLE

Water Treatment

5800 SXT Water Softener

When water quality matters, Pinnacle residential water softeners and filtration systems deliver. Featuring Pentair's patented Fleck technology and backed by superior after-sales support, Pinnacle systems are designed with Canadian families in mind.

Enhance the quality of your water with the Fleck 5800SXT Residential Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

Water treatment solutions engineered for your unique water needs.



Fleck 5800SXT Residential Water Softener

FEATURES

- 5-cycle programming
- Fast-positioning, reversible 10,000 RPM 12-volt DC drive motor
- Seal and spacer cartridge for easy servicing
- LCD backlit display for low-light conditions
- Precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Programming memory backup in case of power loss/outages

SYSTEM INCLUDES

- Control valve featuring SXT electronic timer
- 3/4" turbine water meter
- Poly bypass assembly
- High quality poly glass media vessel with 1" ABS internal distribution
- Brine tank c/w salt shelf and brine safety float assembly
- **High purity, 10% premium grade cation exchange resin or Purolite SSTC-6000 resin**



SPECIFICATIONS

Model Number	Resin (CuFt)	Tank Sizes		Unit Cap		Flow Rates		BKW (GPM)	Salt				Weight (lbs)
		Resin Tank	Brine Tank	Min	Max	Service	Peak		6	9	10	12	
24KX58SXT	0.75	8" x 44"	14" x 34"	19K	24K	4	6	1.5		7		9	85
30KX58SXT	1.0	9" x 48"	14" x 34"	24K	30K	5	7.5	2.0		10		12	95
45KX58SXT	1.5	10" x 54"	14" x 34"	32K	45K	7.5	11.2	2.4		15		18	125
60KX58SXT	2	12" x 52"	18" x 40"	48K	60K	10	15	3.5		20		24	170
75KX58SXT	2.5	13" x 54"	18" x 40"	60K	75K	12.5	18.5	4.0		25		30	200
90KX58SXT	3	14" x 65"	18" x 40"	72K	90K	15	21	5.0		30		36	225
24KSST58SXT	0.75	8" x 44"	14" x 34"	18K	24K	4	6	1.5	4.5		7.5		85
30KSST58SXT	1.0	9" x 48"	14" x 34"	22.5K	30K	5	7.5	2.0	6		10		95
45KSST58SXT	1.5	10" x 54"	14" x 34"	33.5K	45K	7.5	11.2	2.4	9		15		125
60KSST58SXT	2	12" x 52"	18" x 40"	45K	60K	10	15	3.5	12		20		170
75KSST58SXT	2.5	13" x 54"	18" x 40"	56K	75K	12.5	18.5	4.0	15		25		200
90KSST58SXT	3	14" x 65"	18" x 40"	67.5K	90K	15	21	5.0	22.5		30		225

Capacities are based on resin manufacturer's data • Units are set to the factory maximum salt setting • Use maximum capacity when sizing • Flow rates are in U.S. Gallons/minute • Sizes and space requirements are in inches

**SUMMIT
WATER**



www.summitwater.ca



sales@summitwater.ca



519-843-4232



Summit Water