

# PINNACLE

Water Treatment

## 5812 XTR2 Water Softener

When water quality matters, Pinnacle large residential/ light commercial water softeners and filtration systems deliver. Featuring Pentair's patented Fleck technology and backed by superior after-sales support, Pinnacle systems are designed with Canadian families in mind.

Enhance the quality of your water with the Fleck 5812XTR2 Water Softener.

- Silky soft skin & hair after showering
- Clothes are brighter, softer & last longer
- Glasses & dishware are spot free
- Use 50% less detergent, fabric softeners, soap, shampoo & personal moisturizers
- Add years of life to water heaters, dishwashers & washing machines

**Water treatment solutions engineered for your unique water needs.**



# Fleck 5812 XTR2 Large Residential/ Light Commercial Water Softener

## FEATURES

- Premium touchscreen LCD display
- Fast-positioning, reversible 10,000 RPM 12-volt DC drive motor
- Seal and spacer cartridge for easy servicing
- LCD backlit display for low-light conditions
- Precision cycle positioning
- Soft water refill for better brine saturation and cleaner brine tank
- Enhanced service flows up to 43 GPM
- Available in both upflow and downflow
- Programming memory backup in case of power loss/outages

## SYSTEM INCLUDES

- Control valve featuring XTR2 touchscreen
- 1.25" turbine water meter
- 1.25" Poly bypass assembly
- High quality poly glass media vessel with 1.25" ABS internal distribution
- Brine tank c/w salt shelf and brine safety float assembly
- **High purity, 10% premium grade cation exchange resin or Purolite SSTC-6000**



## SPECIFICATIONS

Model Number	Resin (CuFt)	Tank Sizes		Unit Cap		Flow Rates		BW GPM	Salt				Weight (lbs)
		Resin Tank	Brine Tank	Min	Max	Service	Peak		6	9	10	12	
75KX52XTR2	2.5	13" x 54"	18" x 40"	60K	75K	12.5	18.5	4		22.5		30	195
90KX52XTR2	3	14" x 65"	18" x 40"	72K	90K	15	22.5	5		27		36	225
120KX52XTR2	4	16" x 65"	18" x 40"	96K	120K	20	30	7		36		48	280
150KX52XTR2	5	18" x 65"	24" x 48"	120K	150K	25	37.5	9		40		60	350
75SST52XTR2	2.5	13" x 54"	18" x 40"	56K	75K	12.5	18.5	4	15		25		195
90KSST52XTR2	3	14" x 65"	18" x 40"	67.5K	90K	15	22.5	5	18		30		225
120KSST52XTR2	4	16" x 65"	18" x 40"	90K	120K	20	30	7	24		40		280
150KSST52XTR2	5	18" x 65"	24" x 48"	112.5K	150K	25	37.5	9	30		50		350

Capacities are based on resin manufacturer's data • Units are set to the factory maximum salt setting • Use minimum capacity when sizing • Flow rates are in U.S. Gallons/minute • Sizes and space requirements are in inches

**SUMMIT  
WATER**



[www.summitwater.ca](http://www.summitwater.ca)



[sales@summitwater.ca](mailto:sales@summitwater.ca)



519-843-4232



Summit Water